

<b>Frame</b>	Galvanized steel studs and cross profiles.
<b>Skirting</b>	Recessed steel floor tracks or PVC skirting.
<b>Head tracks</b>	Recessed or flush channel steel sections. Picture hooks can be hung from the recessed head tracks.
<b>Panels</b>	12,5 mm plasterboard or chipboard. 2, 3 or 4 panels possible.
<b>Glass elements</b>	Single or double-glazed metal frames, different section forms. Several types and thicknesses of glass available.
<b>Door elements</b>	Metal frames with square, rounded or elliptical corners for standard or floor-to-ceiling height doors, suitable for Maars metal doors. Wooden, fully glazed and sliding doors are also available.
<b>Panel linking</b>	StyleLine Finesse: discreet V-joints without visible connectors. StyleLine Variant: varnished steel omega sections with synthetic infill. StyleLine Standard: recessed steel omega profiles with synthetic cover strips.
<b>Module width</b>	Up to 1200 mm with vertical divisions and up to 1800 mm in the case of horizontal divisions. Other dimensions possible on request.
<b>Partition height</b>	Up to 3000 mm, other heights possible on request.
<b>Partition thickness</b>	82 mm with single cladding, 107 mm with double cladding.
<b>Weight</b>	Solid modules approximately 28 kg/m <sup>2</sup> for single panelled to approximately 48 kg/m <sup>2</sup> for double panelled partitions.
<b>Finish, colour</b>	Metal partition elements, including the Maars metal doors, are finished with a polyester-epoxy powder coating in satin or soft touch in one of our RAL colours. PVC components are also available in a number of RAL colours. Partition cladding finished with vinyl, textile, veneer or melamine. Wooden doors are lacquered, veneered or laminated.
<b>Services</b>	Services can be installed either horizontally or vertically and easily accessed for maintenance or future alteration.
<b>Accessories</b>	Cupboard units, ticket and sliding window units, Venetian and vertical blinds within the sealed glass elements, picture hooks etc.
<b>Sound insulation</b>	Single panelled partitions up to Rw 42 dB, double panelled partitions up to Rw 49 dB. Test reports available on request.
<b>Fire resistance</b>	Solid panelled partitions from 30 minutes up to 60 minutes, window units up to 30 minutes, door units up to 30 minutes. Test reports available on request.

We will be happy to talk to you about special versions such as partitions made from different materials, particular colours, custom finishes etc.